



手轮式(Handwheel)

技术参数(Technical parameters)									
型号(Model)	2	3	4	5	6	6D	7	8	9
速比(Ratio)	30:1	42:1	43:1	54:1	64:1	72:1	77:1	76:1	89:1
输入力矩(Input torque)Nm	40	55	100	100	140	140	165	195	195
输出力矩(Output torque)Nm	380	750	1400	1800	3000	3300	4200	4900	5700
限位调整(Limit adjustment)	±5°	±5°	±5°	±5°	±5°	±5°	±5°	±5°	±5°
蝶阀参配(Butterfly valve)DN	80-100	125-150	200-250	300-350	400-450	450	500-600	700	800
球阀参配(Ball valve)DN	50	80	100	150	200	250	250-300	350	400
连接尺寸(Connection size)									
连接法兰(Flange connction)[D]	90	125	150	175	210	230	260	300	350
连接孔中心(Connecton center)[D1]	70	102	125	140	165	185	200	254	298
法兰凹面(Concave flange)[D2]	55X3	70X3	85X3	100X4	130X5	150X5	160X5	200X5	230X5
孔数-孔径(Amount-aperture)[N-M]	4-M8	4-M10	4-M12	4-M16	4-M20	4-M20	8-M16	8-M16	8-M20
标准轴孔(Standard shaft hole)[d]	16	24	30	36	40	45	50	60	80
可选轴孔(Optional hole-axis)	14、18	22、26	28、32	32、42	38、42	42、8	45、55	55、65	70、75
	20		36	45、48	45、48		58、60	70	82、90
键宽X条数X90° (Key xnumber)[b]	5X1	8X1	10X1	12X1	12X2	14X2	16X2	18X2	22X2
安装高度(Install height)[h]	52	62	68	75	105	110	110	120	120
铸件手轮(Casting handwheel) φ	160	240	280	300	350	400	400	500	500
钢管焊接手轮(pipe welding handwheel) φ	180	240	300	300	400	400	500	600	600
链轮盘(sprocket) φ	200		300			400			
外型尺寸(Appearance size)									
A	190	235	270	320	355	420	420	540	550
B	143	162	182	214	234	270	273	373	353
C	192	265	310	366	420	475	486	580	636
E	130	188	220	260	295	330	340	410	438
H1	65	68	85	95	125	125	130	155	160
箱体外径(DO Box)[Q]	115	150	180	220	250	265	300	340	410

