



型号Model	HQ-4S	HQ-5S	HQ-6S	HQ-7S	HQ-8S	HQ-9S	
技术参数 Technical-parameters							
速比Ratio	1170:1	1426:1	1541:1	1593:1	1560:1	2560:1	
最大转矩 Max-torque N·m	N·m	8000	15000	18000	36000	60000	120000
	Kgf·m	816	1530	1836	3673	6122	1244
机械效率M.A.±10%	105.3	128.3	138.7	150.4	165.5	250.5	
重量Weight Kg	70	93	103	167	221	560	
连接尺寸 Connection-size							
法兰号FLANGE	F25	F30	F35	F40	F48	F60	
法兰外圆(D)	300	350	415	475	560	686	
连接孔中心 PCD	D0	254	298	356	406	483	603
	N-H-DP	8-M16-24	8-M20-30	8-M30-45	8-M36-54	12-M36-54	20-M36-54
凸面Convex (D1×h)	200×5	230×5	260×5	300×8	370×8	470×8	
最大轴杆mm Max-Stem-Diameter	80	105	115	140	155	210	
	22×14	28×16	32×18	36×20	40×22	45×25	
外型尺寸 Appearance-size							
H1	145	160	200	225	270	335	
H2	373	420	495				
K	140	140	179	188	203	215	
K1	80	70	90	100	100	117	
L	155	197	230	264	300	368	
L2	244	286	319	372	410	508	
L3	83	92	92	113	125	155	
L4	230	285	285	330	380	430	
手轮 handwheel	PD	21	21	21	28	28	28
	(b)key	6	6	6	8	8	8
	L0	35	35	35	40	40	40
	M	300	350	400	450	500	600



